

# GRIFLUBE COMPRESSOR OIL SS 400

## Product Benefits:

- Excellent anti-foam properties provide improved oil film strength and heat dissipation
- Readily separates from water for easy removal, which protects against rust and corrosion
- Inhibits oxidation to minimize carbon and varnish buildup
- Anti-corrosion properties protect metal from rust and corrosion

## PRODUCT DESCRIPTION:

Full synthetic, non-detergent compressor oil designed to protect rotary screw air compressors against wear and carbon/varnish buildup.

## APPLICATIONS:

**GRIFLUBE COMPRESSOR OIL SS 400** is designed for use in rotary screw air compressors. Typical service life is 6,000-8,000 hours in normal service.

TEST	ASTM	TYPICAL RESULTS
Stock Code		SS 400
ISO VG	D2422	46
Viscosity 100°C, cST	D445	7.6
Viscosity 40°C, cST	D445	45.7
Viscosity Index	D2270	132
Flash Point, °C (°F) (COC)	D92	250 (482)
Flash Point, °C (°F) (COC)	D92	270 (518)
Pour Point, °C (°F)	D97	-37 (-35)
Four Ball Wear Test, mm soar		
75°C, 1200 rpm, 40 kg, 1 hr	D4172	0.45
Foam Tendency	D892	
SEQ I	-	0/0
SEQ II	-	0/0
SEQ III	-	0/0
Demulsibility	D1404	40-40-0 (15)
Copper Corrosion 121°C, 3 hr	D130	1B
Chemical Properties:		
Metals (wt%)	-	
Phosphorus	-	0.0180%

*The information contained herein is accurate to the best of our knowledge at the time of printing. It is supplied upon the express condition that the customer or user is responsible for determining the product's suitability for a particular purpose. Products purchased from SEVERUS INC. are subject to the terms and conditions set out in the sales contract, quotation, warranty and/or order acknowledgement.*

## PACKAGING:

Pails

## HEALTH & SAFETY

All reasonable care has been taken to ensure that the information contained in this publication is accurate as the date of printing, however, such information might change due to changes in the formulation blend occurring subsequent to the date of printing. The MSDS must be consulted for appropriate information regarding storage, safe handling and storage.

