

RED CHIEF

Ready to Use:

- Use with fine, medium or coarse sands
- Can be applied to Raw Sand, Oil Sand, No Bake & Shell Mold Operations
- Low gas content minimizes metal agitation at pasted joints
- Rapid drying-suitable for pasting warm cores
- Formulated for all metals (pasting applications)
- Also available in a Dry Powder.

PACKAGING:

Drums
Pails

PRODUCT DESCRIPTION:

Hill & Griffith's Red Chief Core Paste is formulated to suit a variety of foundry applications.

READY TO USE:

Use with fine, medium or coarse sands
Can be applied to Raw Sand, Oil Sand, No Bake and Shell Mold Operations
Low gas content minimizes metal agitation at pasted joints
Rapid drying-suitable for pasting warm cores
Formulated for all metals (pasting applications)
Also available in a Dry Powder.

DRY POWDER:

Same characteristics as above
Just mix with 20% water by weight to 80% by weight dry powder.
Baume and strength can be adjusted by additional or less water addition.
Drying times may vary depending on temperature and humidity.

STORAGE:

Typically, the Red Chief has a shelf life of two years. Keep product in a dry, ambient temperature, seal tight container to eliminate evaporation of water. Once material has dried it cannot be reactivated.

HEALTH & SAFETY:

Red Chief has a low degree of hazard. Recommended disposal procedures are landfill, reclaim, and incineration according to local, state and federal regulations. Refer to MSDS for more information.

